

**cmxtnmixlogit postestimation** — Postestimation tools for cmxtnmixlogit

[Postestimation commands](#)   
 [predict](#)   
 [margins](#)   
 [Methods and formulas](#)  
 Also see

## Postestimation commands

The following standard postestimation commands are available after `cmxtnmixogit`:

Command	Description
<code>contrast</code>	contrasts and ANOVA-style joint tests of estimates
<code>estat ic</code>	Akaike's, consistent Akaike's, corrected Akaike's, and Schwarz's Bayesian information criteria (AIC, CAIC, AICc, and BIC)
<code>estat summarize</code>	summary statistics for the estimation sample
<code>estat vce</code>	variance–covariance matrix of the estimators (VCE)
<code>estimates</code>	cataloging estimation results
<code>etable</code>	table of estimation results
* <code>hausman</code>	Hausman's specification test
<code>lincom</code>	point estimates, standard errors, testing, and inference for linear combinations of coefficients
* <code>lrtest</code>	likelihood-ratio test
<code>margins</code>	adjusted predictions, predictive margins, and marginal effects
<code>marginsplot</code>	graph the results from margins (profile plots, interaction plots, etc.)
<code>nlcom</code>	point estimates, standard errors, testing, and inference for nonlinear combinations of coefficients
<code>predict</code>	probabilities, etc.
<code>predictnl</code>	point estimates, standard errors, testing, and inference for generalized predictions
<code>pwcompare</code>	pairwise comparisons of estimates
<code>test</code>	Wald tests of simple and composite linear hypotheses
<code>testnl</code>	Wald tests of nonlinear hypotheses

\*`hausman` and `lrtest` are not appropriate with `svy` estimation results.

## predict

### Description for predict

`predict` creates a new variable containing predictions such as probabilities or linear predictions.

### Menu for predict

Statistics > Postestimation

### Syntax for predict

```
predict [type] newvar [if] [in] [, statistic]
```

```
predict [type] stub* [if] [in], scores
```

<i>statistic</i>	Description
------------------	-------------

---

Main

<code>pr</code>	probability alternative is chosen; the default
<code>xb</code>	linear prediction

---

These statistics are available both in and out of sample; type `predict ... if e(sample) ...` if wanted only for the estimation sample.

`predict` omits missing values casewise if `cmxtmixlogit` used casewise deletion (the default); if `cmxtmixlogit` used alternativewise deletion (option `altwise`), `predict` uses alternativewise deletion.

### Options for predict

Main

---

`pr`, the default, calculates the probability of choosing each alternative.

`xb` calculates the linear prediction.

`scores` calculates the scores for each coefficient in  $e(b)$ . This option requires a new variable list of length equal to the number of columns in  $e(b)$ . Otherwise, use the `stub*` syntax to have `predict` generate enumerated variables with prefix `stub`.

## margins

### Description for margins

`margins` estimates margins of response for probabilities and linear predictions.

### Menu for margins

Statistics > Postestimation

### Syntax for margins

`margins` [*marginlist*] [, *options*]

`margins` [*marginlist*] , predict(*statistic* ...) [predict(*statistic* ...) ...] [*options*]

<i>statistic</i>	Description
<code>pr</code>	probability alternative is chosen; the default
<code>xb</code>	linear prediction
<code>scores</code>	not allowed with <code>margins</code>

Statistics not allowed with `margins` are functions of stochastic quantities other than `e(b)`.

For more details, see [CM] [margins](#).

### Methods and formulas

The predicted probability of case  $i$  choosing alternative  $a$  at time  $t$  is

$$\hat{P}_{iat} = \frac{1}{M} \sum_{m=1}^M P_{iat}(\beta^m)$$

where  $M$  is the number of random draws and  $P_{iat}(\beta^m)$  are the logistic probabilities

$$P_{iat}(\beta^m) = \frac{e^{\mathbf{x}_{iat}\beta_i^m + \mathbf{w}_{iat}\boldsymbol{\alpha} + \mathbf{z}_{it}\boldsymbol{\delta}_a}}{\sum_{a=1}^A e^{\mathbf{x}_{iat}\beta_i^m + \mathbf{w}_{iat}\boldsymbol{\alpha} + \mathbf{z}_{it}\boldsymbol{\delta}_a}}$$

evaluated at the simulated coefficients  $\beta^m$ . The linear predictions are

$$\frac{1}{M} \sum_{m=1}^M \mathbf{x}_{iat}\beta_i^m + \mathbf{w}_{iat}\boldsymbol{\alpha} + \mathbf{z}_{it}\boldsymbol{\delta}_a$$

See [Methods and formulas](#) in [CM] [cmxtnmixlogit](#) for details.

## Also see

[CM] **cmxtmixlogit** — Panel-data mixed logit choice model

[CM] **margins** — Adjusted predictions, predictive margins, and marginal effects

[U] **20 Estimation and postestimation commands**

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2023 StataCorp LLC, College Station, TX, USA. All rights reserved.

For suggested citations, see the FAQ on [citing Stata documentation](#).

