

*added\_line\_options* — Options for adding lines to twoway graphs

Description Remarks and examples	Quick start Reference	Syntax Also see	Options
-------------------------------------	--------------------------	--------------------	---------

## Description

`yline()`, `xline()`, and `tline()` are used with `twoway` to add lines to the plot region. `tline()` is an extension to `xline()`; see [TS] [tline](#) for examples using `tline()`.

## Quick start

Add a horizontal line at the value 0

```
graph_command ... , ... yline(0)
```

Add horizontal lines at the values of 9, 11, and 17

```
graph_command ... , ... yline(9 11 17)
```

Add a vertical line at the value of 17.2

```
graph_command ... , ... xline(17.2)
```

Same as above, but add a thin red line

```
graph_command ... , ... xline(17.2, lwidth(thin) lcolor(red))
```

Same as above, but specify line width as 1 point

```
graph_command ... , ... xline(17.2, lwidth(1pt) lcolor(red))
```

Add a vertical line on June 29, 2016

```
graph_command ... , ... tline(29jun2016)
```

Add a red vertical line at 10 and a blue one at 20

```
graph_command ... , ... xline(10, lcolor(red)) xline(20, lcolor(blue))
```

## Syntax

<i>added_line_options</i>	Description
<u>y</u> line( <i>linearg</i> )	add horizontal lines at specified <i>y</i> values
<u>x</u> line( <i>linearg</i> )	add vertical lines at specified <i>x</i> values
<u>t</u> line( <i>time_linearg</i> )	add vertical lines at specified <i>t</i> -values

`yline()`, `xline()`, and `tline()` are *merged-implicit*; see [G-4] **Concept: repeated options** and see *Interpretation of repeated options* below.

where *linearg* is

```
numlist [ , suboptions ]
```

For a description of *numlist*, see [U] 11.1.8 **numlist**.

and where *time\_linearg* is

```
datelist [ , suboptions ]
```

For a description of *datelist*, see [U] 11.1.9 **datelist**.

<i>suboptions</i>	Description
<u>a</u> xis(#)	which axis to use, $1 \leq \# \leq 9$
<u>s</u> tyl(e)( <i>addedlinestyle</i> )	overall style of added line
[ <u>n</u> o]e <u>xt</u> end	extend line through plot region's margins
<u>l</u> styl(e)( <i>linestyle</i> )	overall style of line
<u>l</u> patt(ern)( <i>linepatternstyle</i> )	line pattern (solid, dashed, etc.)
<u>l</u> widt(h)( <i>linewidthstyle</i> )	thickness of line
<u>l</u> align( <i>linealignmentstyle</i> )	outline alignment (inside, outside, center)
<u>l</u> color( <i>colorstyle</i> )	color and opacity of line

## Options

`yline(linearg)`, `xline(linearg)`, and `tline(time_linearg)` specify the *y*, *x*, and *t* (time) values where lines should be added to the plot.

## Suboptions

`axis(#)` is for use only when multiple *y*, *x*, or *t* axes are being used (see [G-3] *axis\_choice\_options*). `axis()` specifies to which axis the `yline()`, `xline()`, or `tline()` is to be applied.

`style(addedlinestyle)` specifies the overall style of the added line, which includes [no]extend and `lstyle(linestyle)` documented below. See [G-4] *addedlinestyle*. The [no]extend and `lstyle()` options allow you to change the added line's attributes individually, but `style()` is the starting point.

You need not specify `style()` just because there is something that you want to change, and in fact, most people seldom specify the `style()` option. You specify `style()` when another style exists that is exactly what you desire or when another style would allow you to specify fewer changes to obtain what you want.

`extend` and `noextend` specify whether the line should extend through the plot region's margin and touch the axis; see [G-3] [region\\_options](#). Usually `noextend` is the default, and `extend` is the option, but that is determined by the overall `style()` and, of course, the scheme; see [G-4] [Schemes intro](#).

`lstyle(linestyle)`, `lpattern(linepatternstyle)`, `lwidth(linewidthstyle)`, `lalign(linealignmentstyle)`, and `lcolor(colorstyle)` specify the look of the line; see [G-2] [graph twoway line](#). `lstyle()` can be of particular use:

To create a line with the same look as the lines used to draw axes, specify `lstyle(foreground)`.

To create a line with the same look as the lines used to draw grid lines, specify `lstyle(grid)`.

## Remarks and examples

[stata.com](http://www.stata.com)

`ylines()` and `xlines()` add lines where specified. If, however, your interest is in obtaining grid lines, see the `grid` option in [G-3] [axis\\_label\\_options](#).

Remarks are presented under the following headings:

*Typical use*  
*Interpretation of repeated options*

### Typical use

`ylines()` or `xlines()` are typically used to add reference values:

```
. scatter yvar xvar, yline(10)
. scatter yvar year, xline(1944 1989)
```

To give the line in the first example the same look as used to draw an axis, we could specify

```
. scatter yvar xvar, yline(10, lstyle(foreground))
```

If we wanted to give the lines used in the second example the same look as used to draw grids, we could specify

```
. scatter yvar year, xline(1944 1989, lstyle(grid))
```

### Interpretation of repeated options

Options `ylines()` and `xlines()` may be repeated, and each is executed separately. Thus different styles can be used for different lines on the same graph:

```
. scatter yvar year, xline(1944) xline(1989, lwidth(3))
```

## Reference

Cox, N. J. 2009. [Stata tip 82: Grounds for grids on graphs](#). *Stata Journal* 9: 648–651.

## Also see

[G-4] *addedlinestyle* — Choices for overall look of added lines

[G-4] *colorstyle* — Choices for color

[G-4] *linealignmentstyle* — Choices for whether outlines are inside, outside, or centered

[G-4] *linepatternstyle* — Choices for whether lines are solid, dashed, etc.

[G-4] *linestyle* — Choices for overall look of lines

[G-4] *linewidthstyle* — Choices for thickness of lines

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2023 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).