

editmissing() — Edit matrix for missing values

Description
Diagnostics

Syntax
Also see

Remarks and examples

Conformability

Description

`editmissing(A, v)` returns A with any missing values changed to v .

`_editmissing(A, v)` replaces all missing values in A with v .

Syntax

numeric matrix `editmissing(numeric matrix A, numeric scalar v)`

void `_editmissing(numeric matrix a, numeric scalar v)`

Remarks and examples

stata.com

`editmissing()` and `_editmissing()` are very fast.

If you want to change nonmissing values to other values, including missing, see [M-5] [editvalue\(\)](#).

Conformability

`editmissing(A, v):`

A: $r \times c$
v: 1×1
result: $r \times c$

`_editmissing(A, v):`

input:

A: $r \times c$
v: 1×1

output:

A: $r \times c$

Diagnostics

`editmissing(A, v)` and `_editmissing(A, v)` change all missing elements to v , including not only `.` but also `.a`, `.b`, `...`, `.z`.

Also see

[M-5] [editvalue\(\)](#) — Edit (change) values in matrix

[M-4] [Manipulation](#) — Matrix manipulation

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2023 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).