

select() — Select rows, columns, or indices

Description
Diagnostics

Syntax
Also see

Remarks and examples

Conformability

Description

`select(X, v)` returns X

1. omitting the rows for which $v[i]==0$ (v a column vector) or
2. omitting the columns for which $v[j]==0$ (v a row vector).

`st_select(A, X, v)` does the same thing, except that the result is placed in A and, if X is a view, A will be a view.

`selectindex(v)` returns

1. a row vector of column indices j for which $v[j]!=0$ (v a row vector) or
2. a column vector of row indices i for which $v[i]!=0$ (v a column vector).

Syntax

transmorphic matrix `select(transmorphic matrix X, real vector v)`

void `st_select(A, transmorphic matrix X, real vector v)`

real vector `selectindex(real vector v)`

Remarks and examples

Remarks are presented under the following headings:

Examples
Using st_select()

Examples

1. To select rows 1, 2, and 4 of $5 \times c$ matrix X ,

```
submat = select(X, (1\1\0\1\0))
```

See [M-2] **Subscripts** for another solution, `submat = X[(1\2\4), .]`.

2. To select columns 1, 2, and 4 of $r \times 5$ matrix X ,

```
submat = select(X, (1,1,0,1,0))
```

See [M-2] **Subscripts** for another solution, `submat = X[., (1,2,4)]`.

3. To select rows of X for which the first element is positive,

```
submat = select(X, X[:,1]:>0)
```

4. To select columns of X for which the first element is positive,

```
submat = select(X, X[1,:]:>0)
```

5. To select rows of X for which there are no missing values,

```
submat = select(X, rowmissing(X):==0)
```

6. To select rows and columns of square matrix X for which the diagonal elements are positive,

```
pos      = diagonal(X):>0
submat   = select(X, pos)
submat   = select(submat, pos')
```

or, equivalently,

```
pos      = diagonal(X):>0
submat   = select(select(X, pos), pos')
```

7. To select column indices for which $v[j] \neq 0$,

```
: v
      1  2  3  4  5
1  

|   |   |   |   |   |
|---|---|---|---|---|
| 6 | 0 | 7 | 0 | 8 |
|---|---|---|---|---|



: selectindex(v)
      1  2  3
1  

|   |   |   |
|---|---|---|
| 1 | 3 | 5 |
|---|---|---|


```

8. To select row indices for which $v[i] \neq 0$,

```
: w
      1
1  

|   |
|---|
| 0 |
| 3 |
| 0 |
| 2 |
| 1 |



: selectindex(w)
      1
1  

|   |
|---|
| 2 |
| 4 |
| 5 |


```

Using st_select()

Coding

$$\text{st_select}(\text{submat}, X, v) \quad (1)$$

produces the same result as coding

$$\text{submat} = \text{st_select}(X, v) \quad (2)$$

The difference is in how the result is stored. If X is a view (it need not be), then (1) will produce submat as a view or, if you will, a subview, whereas in (2), submat will always be a regular (nonview) matrix.

When X is a view, (1) executes more quickly than (2) and produces a result that consumes less memory.

See [M-5] [st_view\(\)](#) for a description of views.

Conformability

$\text{select}(X, v)$:

X :	$r_1 \times c_1$			
v :	$r_1 \times 1$	or	$1 \times c_1$	
<i>result</i> :	$r_2 \times c_1$	or	$r_1 \times c_2$,	$r_2 \leq r_1, c_2 \leq c_1$

$\text{st_select}(A, X, v)$:

input:

X :	$r_1 \times c_1$		
v :	$r_1 \times 1$	or	$1 \times c_1$

output:

A :	$r_2 \times c_1$	or	$r_1 \times c_2$,	$r_2 \leq r_1, c_2 \leq c_1$
-------	------------------	----	--------------------	------------------------------

$\text{selectindex}(v)$:

v :	$r_1 \times 1$	or	$1 \times c_1$	
<i>result</i> :	$r_2 \times 1$	or	$1 \times c_2$,	$r_2 \leq r_1, c_2 \leq c_1$

Diagnostics

None.

Also see

[M-5] [st_subview\(\)](#) — Make view from view

[M-2] [op_colon](#) — Colon operators

[M-2] [Subscripts](#) — Use of subscripts

[M-4] [Utility](#) — Matrix utility functions

4 `select()` — Select rows, columns, or indices

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2023 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).