

mlexp postestimation — Postestimation tools for mlexp

[Postestimation commands](#)
 [predict](#)
 [margins](#)
 [Also see](#)

Postestimation commands

The following postestimation commands are available after `mlexp`:

Command	Description
<code>contrast</code>	contrasts and ANOVA-style joint tests of estimates
<code>estat ic</code>	Akaike's, consistent Akaike's, corrected Akaike's, and Schwarz's Bayesian information criteria (AIC, CAIC, AICC, and BIC)
<code>estat summarize</code>	summary statistics for the estimation sample
<code>estat vce</code>	variance–covariance matrix of the estimators (VCE)
<code>estimates</code>	cataloging estimation results
<code>etable</code>	table of estimation results
<code>lincom</code>	point estimates, standard errors, testing, and inference for linear combinations of coefficients
* <code>lrtest</code>	likelihood-ratio test
<code>margins</code>	marginal means, predictive margins, marginal effects, and average marginal effects
<code>marginsplot</code>	graph the results from margins (profile plots, interaction plots, etc.)
<code>nlcom</code>	point estimates, standard errors, testing, and inference for nonlinear combinations of coefficients
<code>predict</code>	linear predictions and scores
<code>predictnl</code>	point estimates, standard errors, testing, and inference for generalized predictions
<code>pwcompare</code>	pairwise comparisons of estimates
<code>suest</code>	seemingly unrelated estimation
<code>test</code>	Wald tests of simple and composite linear hypotheses
<code>testnl</code>	Wald tests of nonlinear hypotheses

*`lrtest` is not appropriate with `svy` estimation results.

predict

Description for predict

`predict` creates a new variable containing predictions such as linear predictions and equation-level scores.

Menu for predict

Statistics > Postestimation

Syntax for predict

```
predict [type] newvar [if] [in] [, xb equation(#eqno | eqname) ]
```

```
predict [type] stub* [if] [in], scores
```

Scores are only available for observations within the estimation sample.

Options for predict

`xb` calculates the linear prediction.

`equation(#eqno | eqname)` specifies the equation for which the linear prediction is desired. Specifying `equation(#1)` indicates that the calculation be made for the first equation. Specifying `equation(demand)` indicates that the calculation be made for the equation named `demand`, assuming there is an equation named `demand` in the model.

If you specify one new variable name and omit `equation()`, results are the same as if you had specified `equation(#1)`.

For more information on using `predict` after multiple-equation estimation commands, see [\[R\] predict](#).

`scores` calculates the equation-level score variables. The *j*th new variable will contain the scores for the *j*th equation of the model.

margins

Description for margins

`margins` estimates margins of response for linear predictions.

Menu for margins

Statistics > Postestimation

Syntax for margins

```
margins [marginlist] [, options]
```

```
margins [marginlist] , predict(statistic ...) [predict(statistic ...) ...] [options]
```

<i>statistic</i>	Description
------------------	-------------

<code>xb</code>	linear prediction
-----------------	-------------------

`xb` defaults to the first equation.

Also see

[R] [mlexp](#) — Maximum likelihood estimation of user-specified expressions

[U] [20 Estimation and postestimation commands](#)

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2023 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the [FAQ on citing Stata documentation](#).