

eivreg postestimation — Postestimation tools for eivreg

[Postestimation commands](#)
 [predict](#)
 [margins](#)
 [Remarks and examples](#)
 Also see

Postestimation commands

The following postestimation commands are available after `eivreg`:

Command	Description
<code>contrast</code>	contrasts and ANOVA-style joint tests of estimates
<code>estat summarize</code>	summary statistics for the estimation sample
<code>estat vce</code>	variance–covariance matrix of the estimators (VCE)
<code>estimates</code>	cataloging estimation results
<code>etable</code>	table of estimation results
<code>lincom</code>	point estimates, standard errors, testing, and inference for linear combinations of coefficients
<code>margins</code>	marginal means, predictive margins, marginal effects, and average marginal effects
<code>marginsplot</code>	graph the results from margins (profile plots, interaction plots, etc.)
<code>nlcom</code>	point estimates, standard errors, testing, and inference for nonlinear combinations of coefficients
<code>predict</code>	linear predictions
<code>pwcompare</code>	pairwise comparisons of estimates
<code>test</code>	Wald tests of simple and composite linear hypotheses
<code>testnl</code>	Wald tests of nonlinear hypotheses

predict

Description for predict

`predict` creates a new variable containing the linear prediction assuming that values of the covariates used for the prediction were measured without error.

Menu for predict

Statistics > Postestimation

Syntax for predict

```
predict [type] newvar [if] [in]
```

Available both in and out of sample; type `predict ... if e(sample) ...` if wanted only for the estimation sample.

margins

Description for margins

`margins` estimates margins of response for linear predictions.

Menu for margins

Statistics > Postestimation

Syntax for margins

```
margins [marginlist] [, options]
```

Remarks and examples

[stata.com](http://www.stata.com)

▶ Example 1

We return to [example 1](#) from [R] `eivreg`:

```
. use https://www.stata-press.com/data/r18/auto
(1978 automobile data)
. eivreg price weight foreign, reliab(weight .85)
```

Errors-in-variables regression

Variable	Assumed reliability			
weight	0.8500		Number of obs	= 74
*	1.0000		F(2, 71)	= 18.46
			Prob > F	= 0.0000
			R-squared	= 0.6483
			Root MSE	= 1773.54

price	Coefficient	Std. err.	t	P> t	[95% conf. interval]	
weight	4.31985	.7134251	6.06	0.000	2.89732	5.742379
foreign	4637.32	849.0221	5.46	0.000	2944.418	6330.222
_cons	-8257.017	2390.337	-3.45	0.001	-13023.21	-3490.821

We wish to predict the price of a foreign car that weighs 2,300 pounds. We can use `predict` because 2,300 pounds is the true weight, not the result of an error-prone measurement.

To make this prediction, first we add the new observation to the dataset.

```
. set obs 75
Number of observations (_N) was 74, now 75.
. replace foreign = 1 in 75
(1 real change made)
. replace weight = 2300 in 75
(1 real change made)
```

Now, we use `predict` to predict the price of the car.

```
. predict newprice in 75
(option xb assumed; fitted values)
(74 missing values generated)
(predictions assume covariates measured without error)
. list weight foreign newprice in 75
```

	weight	foreign	newprice
75.	2,300	Foreign	6315.957

`predict` issued a note reminding us that the computed predictions assume that the covariates used for prediction are measured without error. In general, you should avoid using `predict` to obtain in-sample predictions unless you first replace the measurement-error covariates with values that are error free.

◀

Also see

[R] [eivreg](#) — Errors-in-variables regression

[U] [20 Estimation and postestimation commands](#)

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2023 StataCorp LLC, College Station, TX, USA. All rights reserved.

