

**set showbaselevels** — Display settings for coefficient tables

[Description](#)[Syntax](#)[Option](#)[Remarks and examples](#)[Also see](#)

## Description

`set showbaselevels` specifies whether to display base levels of factor variables and their interactions in coefficient tables. `set showbaselevels on` specifies that base levels be reported for factor variables and for interactions whose bases cannot be inferred from their component factor variables. `set showbaselevels all` specifies that all base levels of factor variables and interactions be reported.

`set showemptycells` specifies whether to display empty cells in coefficient tables.

`set showomitted` specifies whether to display omitted coefficients in coefficient tables.

`set fvlabel` specifies whether to display factor-variable value labels in coefficient tables. `set fvlabel on`, the default, specifies that the labels be displayed. `set fvlabel off` specifies that the levels of factor variables rather than the labels be displayed.

`set fvwrap #` specifies that long value labels wrap # lines in the coefficient table. The default is `set fvwrap 1`, which means that long value labels will be abbreviated to fit on one line.

`set fvwrapon` specifies whether value labels that wrap will break at word boundaries or break based on available space. `set fvwrapon word`, the default, specifies that value labels break at word boundaries. `set fvwrapon width` specifies that value labels break based on available space.

## Syntax

```
set showbaselevels {on|off|all} [, permanently]
```

```
set showemptycells {on|off} [, permanently]
```

```
set showomitted {on|off} [, permanently]
```

```
set fvlabel {on|off} [, permanently]
```

```
set fvwrap # [, permanently]
```

```
set fvwrapon {word|width} [, permanently]
```

## Option

`permanently` specifies that, in addition to making the change right now, the setting be remembered and become the default setting when you invoke Stata.

## Remarks and examples

## ► Example 1

We illustrate the first three set commands using cholesterol2.dta.

```
. use https://www.stata-press.com/data/r18/cholesterol2
(Artificial cholesterol data, empty cells)
. generate x = race
. regress chol race##agegrp x
note: 2.race#2.agegrp identifies no observations in the sample.
note: x omitted because of collinearity.
```

Source	SS	df	MS	Number of obs	=	70
				F(13, 56)	=	13.51
Model	15751.6113	13	1211.66241	Prob > F	=	0.0000
Residual	5022.71559	56	89.6913498	R-squared	=	0.7582
				Adj R-squared	=	0.7021
Total	20774.3269	69	301.077201	Root MSE	=	9.4706

chol	Coefficient	Std. err.	t	P> t	[95% conf. interval]	
race						
White	12.84185	5.989703	2.14	0.036	.8430383	24.84067
Other	-.167627	5.989703	-0.03	0.978	-12.16644	11.83119
agegrp						
20-29	17.24681	5.989703	2.88	0.006	5.247991	29.24562
30-39	31.43847	5.989703	5.25	0.000	19.43966	43.43729
40-59	34.86613	5.989703	5.82	0.000	22.86732	46.86495
60-79	44.43374	5.989703	7.42	0.000	32.43492	56.43256
race#agegrp						
White#20-29	0	(empty)				
White#30-39	-22.83983	8.470719	-2.70	0.009	-39.80872	-5.870939
White#40-59	-14.67558	8.470719	-1.73	0.089	-31.64447	2.293306
White#60-79	-10.51115	8.470719	-1.24	0.220	-27.48004	6.457735
Other#20-29	-6.054425	8.470719	-0.71	0.478	-23.02331	10.91446
Other#30-39	-11.48083	8.470719	-1.36	0.181	-28.44971	5.488063
Other#40-59	-.6796112	8.470719	-0.08	0.936	-17.6485	16.28928
Other#60-79	-1.578052	8.470719	-0.19	0.853	-18.54694	15.39084
x	0	(omitted)				
_cons	175.2309	4.235359	41.37	0.000	166.7464	183.7153

```
. set showemptycells off
. set showomitted off
. set showbaselevels all
```

```
. regress chol race##agegrp x
note: 2.race#2.agegrp identifies no observations in the sample.
note: x omitted because of collinearity.
```

Source	SS	df	MS	Number of obs	=	70
Model	15751.6113	13	1211.66241	F(13, 56)	=	13.51
Residual	5022.71559	56	89.6913498	Prob > F	=	0.0000
				R-squared	=	0.7582
				Adj R-squared	=	0.7021
Total	20774.3269	69	301.077201	Root MSE	=	9.4706

chol	Coefficient	Std. err.	t	P> t	[95% conf. interval]	
race						
Black	0	(base)				
White	12.84185	5.989703	2.14	0.036	.8430383	24.84067
Other	-.167627	5.989703	-0.03	0.978	-12.16644	11.83119
agegrp						
10-19	0	(base)				
20-29	17.24681	5.989703	2.88	0.006	5.247991	29.24562
30-39	31.43847	5.989703	5.25	0.000	19.43966	43.43729
40-59	34.86613	5.989703	5.82	0.000	22.86732	46.86495
60-79	44.43374	5.989703	7.42	0.000	32.43492	56.43256
race#agegrp						
Black#10-19	0	(base)				
Black#20-29	0	(base)				
Black#30-39	0	(base)				
Black#40-59	0	(base)				
Black#60-79	0	(base)				
White#10-19	0	(base)				
White#30-39	-22.83983	8.470719	-2.70	0.009	-39.80872	-5.870939
White#40-59	-14.67558	8.470719	-1.73	0.089	-31.64447	2.293306
White#60-79	-10.51115	8.470719	-1.24	0.220	-27.48004	6.457735
Other#10-19	0	(base)				
Other#20-29	-6.054425	8.470719	-0.71	0.478	-23.02331	10.91446
Other#30-39	-11.48083	8.470719	-1.36	0.181	-28.44971	5.488063
Other#40-59	-.6796112	8.470719	-0.08	0.936	-17.6485	16.28928
Other#60-79	-1.578052	8.470719	-0.19	0.853	-18.54694	15.39084
_cons	175.2309	4.235359	41.37	0.000	166.7464	183.7153

#### 4 set showbaselevels — Display settings for coefficient tables

To restore the display of empty cells, omitted predictors, and baselevels to their command-specific default behavior, type

```
. set showemptycells
. set showomitted
. set showbaselevels
. regress chol race##agegrp x
note: 2.race#2.agegrp identifies no observations in the sample.
note: x omitted because of collinearity.
```

Source	SS	df	MS	Number of obs	=	70
Model	15751.6113	13	1211.66241	F(13, 56)	=	13.51
Residual	5022.71559	56	89.6913498	Prob > F	=	0.0000
				R-squared	=	0.7582
				Adj R-squared	=	0.7021
Total	20774.3269	69	301.077201	Root MSE	=	9.4706

chol	Coefficient	Std. err.	t	P> t	[95% conf. interval]	
race						
White	12.84185	5.989703	2.14	0.036	.8430383	24.84067
Other	-.167627	5.989703	-0.03	0.978	-12.16644	11.83119
agegrp						
20-29	17.24681	5.989703	2.88	0.006	5.247991	29.24562
30-39	31.43847	5.989703	5.25	0.000	19.43966	43.43729
40-59	34.86613	5.989703	5.82	0.000	22.86732	46.86495
60-79	44.43374	5.989703	7.42	0.000	32.43492	56.43256
race#agegrp						
White#20-29	0 (empty)					
White#30-39	-22.83983	8.470719	-2.70	0.009	-39.80872	-5.870939
White#40-59	-14.67558	8.470719	-1.73	0.089	-31.64447	2.293306
White#60-79	-10.51115	8.470719	-1.24	0.220	-27.48004	6.457735
Other#20-29	-6.054425	8.470719	-0.71	0.478	-23.02331	10.91446
Other#30-39	-11.48083	8.470719	-1.36	0.181	-28.44971	5.488063
Other#40-59	-.6796112	8.470719	-0.08	0.936	-17.6485	16.28928
Other#60-79	-1.578052	8.470719	-0.19	0.853	-18.54694	15.39084
x						
_cons	0 (omitted)					
	175.2309	4.235359	41.37	0.000	166.7464	183.7153

## ▷ Example 2

We illustrate the last three set commands using jaw.dta.

```
. use https://www.stata-press.com/data/r18/jaw, clear
(Table 4.6. Two-way unbalanced data for fractures of the jaw, Rencher (1998))
. mvreg y1 y2 y3 = i.fracture
```

Equation	Obs	Parms	RMSE	"R-sq"	F	P>F
y1	27	3	10.42366	0.2966	5.060804	0.0147
y2	27	3	6.325398	0.1341	1.858342	0.1777
y3	27	3	5.976973	0.1024	1.368879	0.2735

  

	Coefficient	Std. err.	t	P> t	[95% conf. interval]	
y1						
fracture						
Two compou..	-8.833333	4.957441	-1.78	0.087	-19.06499	1.398322
One simple..	6	5.394759	1.11	0.277	-5.134235	17.13423
_cons	37	3.939775	9.39	0.000	28.8687	45.1313
y2						
fracture						
Two compou..	-5.761905	3.008327	-1.92	0.067	-11.97079	.446977
One simple..	-3.053571	3.273705	-0.93	0.360	-9.810166	3.703023
_cons	38.42857	2.390776	16.07	0.000	33.49425	43.36289
y3						
fracture						
Two compou..	4.261905	2.842618	1.50	0.147	-1.60497	10.12878
One simple..	.9285714	3.093377	0.30	0.767	-5.455846	7.312989
_cons	58.57143	2.259083	25.93	0.000	53.90891	63.23395

## 6 set showbaselevels — Display settings for coefficient tables

```
. set fvwrap 2
```

```
. mvreg y1 y2 y3 = i.fracture
```

Equation	Obs	Parms	RMSE	"R-sq"	F	P>F
y1	27	3	10.42366	0.2966	5.060804	0.0147
y2	27	3	6.325398	0.1341	1.858342	0.1777
y3	27	3	5.976973	0.1024	1.368879	0.2735

	Coefficient	Std. err.	t	P> t	[95% conf. interval]	
y1						
fracture						
Two compound fractures	-8.833333	4.957441	-1.78	0.087	-19.06499	1.398322
One simple fracture	6	5.394759	1.11	0.277	-5.134235	17.13423
_cons	37	3.939775	9.39	0.000	28.8687	45.1313
y2						
fracture						
Two compound fractures	-5.761905	3.008327	-1.92	0.067	-11.97079	.446977
One simple fracture	-3.053571	3.273705	-0.93	0.360	-9.810166	3.703023
_cons	38.42857	2.390776	16.07	0.000	33.49425	43.36289
y3						
fracture						
Two compound fractures	4.261905	2.842618	1.50	0.147	-1.60497	10.12878
One simple fracture	.9285714	3.093377	0.30	0.767	-5.455846	7.312989
_cons	58.57143	2.259083	25.93	0.000	53.90891	63.23395

```
. set fvwrapon width
```

```
. mvreg y1 y2 y3 = i.fracture
```

Equation	Obs	Parms	RMSE	"R-sq"	F	P>F
y1	27	3	10.42366	0.2966	5.060804	0.0147
y2	27	3	6.325398	0.1341	1.858342	0.1777
y3	27	3	5.976973	0.1024	1.368879	0.2735

	Coefficient	Std. err.	t	P> t	[95% conf. interval]		
y1							
fracture							
Two compound fractures	-8.833333	4.957441	-1.78	0.087	-19.06499	1.398322	
One simple fracture		6	5.394759	1.11	0.277	-5.134235	17.13423
_cons		37	3.939775	9.39	0.000	28.8687	45.1313
y2							
fracture							
Two compound fractures	-5.761905	3.008327	-1.92	0.067	-11.97079	.446977	
One simple fracture	-3.053571	3.273705	-0.93	0.360	-9.810166	3.703023	
_cons	38.42857	2.390776	16.07	0.000	33.49425	43.36289	
y3							
fracture							
Two compound fractures	4.261905	2.842618	1.50	0.147	-1.60497	10.12878	
One simple fracture	.9285714	3.093377	0.30	0.767	-5.455846	7.312989	
_cons	58.57143	2.259083	25.93	0.000	53.90891	63.23395	

## 8 set showbaselevels — Display settings for coefficient tables

```
. set fvlabel off
```

```
. mvreg y1 y2 y3 = i.fracture
```

Equation	Obs	Parms	RMSE	"R-sq"	F	P>F
y1	27	3	10.42366	0.2966	5.060804	0.0147
y2	27	3	6.325398	0.1341	1.858342	0.1777
y3	27	3	5.976973	0.1024	1.368879	0.2735

	Coefficient	Std. err.	t	P> t	[95% conf. interval]	
y1						
fracture						
2	-8.833333	4.957441	-1.78	0.087	-19.06499 1.398322	
3	6	5.394759	1.11	0.277	-5.134235 17.13423	
_cons	37	3.939775	9.39	0.000	28.8687 45.1313	
y2						
fracture						
2	-5.761905	3.008327	-1.92	0.067	-11.97079 .446977	
3	-3.053571	3.273705	-0.93	0.360	-9.810166 3.703023	
_cons	38.42857	2.390776	16.07	0.000	33.49425 43.36289	
y3						
fracture						
2	4.261905	2.842618	1.50	0.147	-1.60497 10.12878	
3	.9285714	3.093377	0.30	0.767	-5.455846 7.312989	
_cons	58.57143	2.259083	25.93	0.000	53.90891 63.23395	



To restore these last three set commands to their defaults, type

```
. set fvlabel on
. set fvwrap 1
. set fvwrapon word
. mvreg y1 y2 y3 = i.fracture
```

Equation	Obs	Parms	RMSE	"R-sq"	F	P>F
y1	27	3	10.42366	0.2966	5.060804	0.0147
y2	27	3	6.325398	0.1341	1.858342	0.1777
y3	27	3	5.976973	0.1024	1.368879	0.2735

	Coefficient	Std. err.	t	P> t	[95% conf. interval]	
y1						
fracture						
Two compou..	-8.833333	4.957441	-1.78	0.087	-19.06499 1.398322	
One simple..	6	5.394759	1.11	0.277	-5.134235 17.13423	
_cons	37	3.939775	9.39	0.000	28.8687 45.1313	
y2						
fracture						
Two compou..	-5.761905	3.008327	-1.92	0.067	-11.97079 .446977	
One simple..	-3.053571	3.273705	-0.93	0.360	-9.810166 3.703023	
_cons	38.42857	2.390776	16.07	0.000	33.49425 43.36289	
y3						
fracture						
Two compou..	4.261905	2.842618	1.50	0.147	-1.60497 10.12878	
One simple..	.9285714	3.093377	0.30	0.767	-5.455846 7.312989	
_cons	58.57143	2.259083	25.93	0.000	53.90891 63.23395	

4

## Also see

[R] [set](#) — Overview of system parameters

[R] [query](#) — Display system parameters

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2023 StataCorp LLC, College Station, TX, USA. All rights reserved.

